













Intrusion






Please check if products are available in your country before you place your order

Vendor	Description	Product code	
Glassbreak and Shock Detectors			
<i>Glassbreak detectors</i>			
Honeywell	FG1608AS Acoustic Glassbreak Detector with magnetic contact, range 2.4m, for glass thickness 2.4 - 6.4mm, suitable for single, toughened, laminated, wired, coated and double-glazed glass (min. dim. 15x22cm), tamper switch, supply 7-18VDC	FG1608AS	
ROKONET K I S E D G R O U P	RG71FM Vitron Glassbreak Detector range 9m, with cover for flush mount	RG71FM	
Honeywell	FG1625TAS Acoustic Glassbreak Detector range 7.6m, for glass thickness 2 - 14mm, suitable for single, toughened, laminated, wired, coated and double-glazed glass (min. dim. 28x28cm), LED alarm memory, supply 6-18VDC	FG1625TAS	
Honeywell	FG1025Z Acoustic Glassbreak Detector range 7.6m, for glass thickness 2 - 14mm, suitable for single, toughened, coated and double-glazed glass (min. dim. 28x28cm), tamper switch, supply 8-14VDC	FG1025Z	
<i>Shock detectors</i>			
ROKONET K I S E D G R O U P	ShockTec Digital Shock Detector white, range (depending on material) 1.5-4m, adjustable sensitivity, supply 9-16VDC	RK600S0000A	
Honeywell	Viper GL Vibration Contact white, range 2.5m, adjustable sensitivity, 9.5-15VDC	HL-900320	
Honeywell	Viper GLX Vibration Contact white, first alarm and ID compatible, range 2.5m, adjustable sensitivity, 9.5-15VDC	HL-900020	
ROKONET K I S E D G R O U P	ShockTec Digital Shock Detector with Magnetic Contact white, range (depending on material) 1.5-4m, adjustable sensitivity, supply 9-16VDC	RK600SM0000A	
Honeywell	Viper GLX Plus Vibration Contact with magnetic contact, white, range 2.5m, adjustable sensitivity, supply 9.5-15VDC	HL-900420	
 COOPER Menvier	447B Shock Detector white, with tamper contact, 9.5-15VDC, IP40	447B	
Honeywell	UN3 Vault Detector range 13m ² , power supply 9-15VDC, with tamper switch	UN3	

Intrusion



Please check if products are available in your country before you place your order

Vendor	Description	Product code	
Glassbreak and Shock Detectors			
Accessories			
Honeywell	FG701 Universal Glassbreak Simulator	FG701	
RKONET <small>KONIG GROUP</small>	RG65 Vitron Glassbreak Simulator	RG65	
Honeywell	Mounting Base for UN3 vault detector	UN300	
Honeywell	Viper Tester	HL-6138	