












# Sound & Communications



PLEASE CHECK IF PRODUCTS ARE AVAILABLE IN YOUR COUNTRY BEFORE YOU PLACE YOUR ORDERS

Vendor	Description	ADI Part number	
<b>1. SPEAKERS</b>			
<b>In Wall / In Ceiling Mount</b>			
<b>5.25" Ceiling Mount</b>			
<i>Proficient</i>	<b>C500 75W 5-1/4" Ceiling Speakers Pair</b> with woofer and 1/2" pivoting tweeter Freq Res: 40Hz - 20Khz, Sensitivity: 90dB 1W/1m, 8Ω Ceiling cut out: 6-11/16" Diameter: 7-3/4". Depth: 3-1/4"	<b>C1-C500</b>	
<i>Phoenix Gold</i>	<b>ATC5 5.25" 2 Way In-Ceiling Speakers Pair</b> with 1" pivoting tweeter, Sensitivity: 90dB 1W/1m Cut Out Dimensions: 6-9/16" diameter Mounting Depth: 2-3/4"	<b>PH-ATC5</b>	
<b>6.5" Ceiling Mount</b>			
<i>Phoenix Gold</i>	<b>ATC6 6.5" 2 Way In-Ceiling Speakers - Pair</b> with 1" pivoting tweeter, Sensitivity: 90dB 1W/1m Cut Out Dimensions: 7 5/8 in diameter, Mounting Depth: 3-3/8"	<b>PH-ATC6</b>	
<i>Phoenix Gold</i>	<b>ATC6DM 6.5" Voice Coil Single Speaker (x1)</b> with Dual angled 1" ferro-fluid tweeters, Summed mono in-ceiling speaker, Sensitivity: 86/89dB 1W/1m Cut Out Dimensions: 7-5/8" in diameter, Mounting Depth: 3-3/8"	<b>PH-ATC6DM</b>	
<i>Proficient</i>	<b>C600TT 75W 6-1/2" Dual Tweeter Ceiling (x1)</b> with twin, hard dome, non pivoting tweeters Freq Res: 36Hz - 20Khz, Sensitivity: 92dB 1W/1m, 8Ω Ceiling cut out: 8-1/4" Diameter: 9-1/4", Depth: 3-5/8"	<b>C1-C600TT</b>	
<i>Proficient</i>	<b>C650 100W 6-1/2" LCR Ceiling Speaker (x1)</b> with woofer and tweeter fixed at 15° angle Freq Res: 40Hz - 20Khz, Sensitivity: 91dB 1W/1m, 8Ω Ceiling cut out: 8-1/4" Diameter: 9-1/4", Depth: 4-9/16"	<b>C1-C650</b>	
<i>Proficient</i>	<b>C610 85W 6-1/2" Ceiling Speakers - Pair</b> with woofer and 1" pivoting tweeter Freq Res: 40Hz - 20Khz, Sensitivity: 91dB 1W/1m, 8Ω Ceiling cut out: 8-1/4" Diameter: 9-1/4", Depth: 3-5/8"	<b>C1-C610</b>	
<i>Proficient</i>	<b>C620 100W 6-1/2" Ceiling Speakers - Pair</b> with woofer and 1" pivoting tweeter Freq Res: 36Hz - 20Khz, Sensitivity: 91dB 1W/1m, 8Ω Ceiling cut out: 8-1/4" Diameter: 9-1/4", Depth: 3-5/8"	<b>C1-C620</b>	
<i>JBL</i>	<b>SP6C SoundPoint™ - Pair</b> <b>2-way 6½" In-ceiling Speaker 80 Watts -</b> Freq Res: 40Hz - 20KHz, one woofer & 1" swivel mounted tweeter, 88dB, Dimensions: 9-3/16" diameter (depth: 4-1/4"), Cut out size: 7-7/8" diameter (White)	<b>JB-SP6C</b>	
<b>8" Ceiling Mount</b>			
<i>Phoenix Gold</i>	<b>ATC8DM 8" Voice Coil Single Speaker (x1)</b> with Dual 1" pivoting tweeters, Summed mono in-ceiling speaker, Sensitivity: 86/89dB 1W/1m, Cut out 9-5/16" diameter, Mounting Depth: 3-3/8"	<b>PH-ATC8DM</b>	
<i>Proficient</i>	<b>C790 125W 8" Ceiling Speaker - Pair</b> with woofer and 1" pivoting tweeter Freq Res: 36Hz - 22Khz, Sensitivity: 92dB 1W/1m, 8Ω Ceiling cut out: 9-7/8" Diameter: 11-1/8", Depth: 4-1/4"	<b>C1-C790</b>	

Version x.x Month 200X

ADI is a tradename of Honeywell XXXXXXXXXXXX.

ADI reserves the right for data changes and/or printing errors.

# Sound & Communications



PLEASE CHECK IF PRODUCTS ARE AVAILABLE IN YOUR COUNTRY BEFORE YOU PLACE YOUR ORDERS

Vendor	Description	ADI Part number	
<i>Proficient</i>	<b>C800TT 150W 8" Dual Tweeter Ceiling (x1)</b> with twin, hard dome, non pivoting tweeters Freq Res: 28Hz - 22Khz, Sensitivity: 92dB 1W/1m, 8Ω Ceiling cut out: 9-7/8" Diameter: 11-1/8", Depth: 4-1/4"	<b>C1-C800TT</b>	
<i>Phoenix Gold</i>	<b>ATC8 8" 2 Way In-Ceiling Speaker - Pair</b> with 1" pivoting tweeter, Sensitivity: 90dB 1W/1m, Cut Out Dimensions: 9-5/16" diameter, Mounting Depth: 3-3/8"	<b>PH-ATC8</b>	
<i>JBL</i>	<b>SP8C SoundPoint™ - Pair</b> <b>2-way 8" In-ceiling Loudspeaker, 100 Watts</b> Freq Res: 30Hz - 20KHz, one woofer & 1" swivel mounted tweeter, 88dB, Dimentions: 10-7/8" diameter (depth: 4-1/4"), Cut out size: 9-1/2" diameter (White)	<b>JB-SP8C</b>	
<i>Proficient</i>	<b>C870 175W 8" LCR Ceiling Speaker (x1)</b> with woofer and tweeter fixed at 15° angle Freq Res: 28Hz - 22Khz, Sensitivity: 92dB 1W/1m, 8Ω Ceiling cut out: 8 7/8" Diameter: 11 1/8, Depth: 5 7/8"	<b>C1-C870</b>	
<i>Proficient</i>	<b>C800 150W 8" Ceiling Speakers - Pair</b> with woofer and 1" pivoting tweeter, bass & treble contour switches, Freq Res: 28Hz - 22Khz, Sensitivity: 92dB 1W/1m, 8Ω Ceiling cut out: 9-7/8" Diameter: 11-1/8", Depth: 4-1/4"	<b>C1-C800</b>	
<b>In-Wall Mount</b>			
<i>Proficient</i>	<b>W665 75W 6-1/2" Wall Speakers - Pair</b> with woofer and 3/4" pivoting tweeter Freq Res: 45Hz - 20Khz, Sensitivity: 90dB 1W/1m, 8Ω Dimensions: (HxWxD) 12-1/4" x 8-3/16" x 3-3/16" Wall cut out: (HxW) 10-7/8" x 6-3/4"	<b>C1-W665</b>	
<i>JBL</i>	<b>SP5 SoundPoint™ - Pair</b> <b>5 1/4" 2 Way, In-wall Loudspeaker 80 Watts</b> Freq Res: 45Hz - 20KHz, one woofer & 1" swivel mounted tweeter, 60 Watts, 87dB, Cut out size: (WxH) 6-1/8" x 8-11/16" Dimentions: (WxHxD) 7-1/2" x 10" x 3-3/4" (White)	<b>JB-SP5</b>	
<i>Proficient</i>	<b>W670 100W 6-1/2" Wall Speakers - Pair</b> with woofer and 1" pivoting tweeter Freq Res: 36Hz - 20Khz, Sensitivity: 91dB 1W/1m, 8Ω Dimensions: (HxWxD) 12-1/4" x 8-3/16" x 3-3/16" Wall cut out: (HxW) 10-7/8" x 6-3/4"	<b>C1-W670</b>	
<i>Proficient</i>	<b>W800 150W 8" Wall Speaker - Pair</b> with woofer and 1" pivoting tweeter, bass & treble contour switches, Freq Res: 28Hz - 22Khz, Sensitivity: 92dB 1W/1m, 8Ω Dimensions: (HxWxD) 14-7/8" x 10-1/8" x 3-3/4" Wall cut out: (HxW) 13-5/8" x 8-3/4"	<b>C1-W800</b>	
<b>Ceiling / In-Wall Speaker Accessories</b>			
<i>JBL</i>	<b>RIF5</b> Rough-In Frame Kit for JBL SP5 Pair - Colour : White	<b>JB-RIF5</b>	
<i>JBL</i>	<b>RIF6C</b> Rough-In Frame Kit for JBL HTI6C/SP6C Pair - Colour : White	<b>JB-RIF6C</b>	
<i>JBL</i>	<b>RIF8C</b> Rough-In Frame Kit for JBL SP8C Pair - Colour : White	<b>JB-RIF8C</b>	

Version x.x Month 200X

ADI is a tradename of Honeywell XXXXXXXXXXXX.

ADI reserves the right for data changes and/or printing errors.

# Sound & Communications



PLEASE CHECK IF PRODUCTS ARE AVAILABLE IN YOUR COUNTRY BEFORE YOU PLACE YOUR ORDERS

Vendor	Description	ADI Part number	
Proficient	<b>Metal Backbox for 6" Ceiling Speaker (x1)</b> for C650, C660 LCR speakers ceiling speakers and C605, C610, C620, C640, C645 and C600TT speakers, includes clips for CMB 24 mounting bars	C1-BB-C650	
Proficient	<b>Metal Backbox for 8" Ceiling Speaker (x1)</b> for C790, C800, C850, C870, C800TT and C850TT ceiling speakers	C1-BB-C800	
Proficient	<b>Metal Backbox for 6" In-wall Speaker (x1)</b> for W665, W670, W680 and w690 in-wall speakers	C1-BB-W600	
<b>Surface Mount</b>			
JBL	<b>Control One Control® Series - Pair</b> Pair of 2-way 4" Control Monitor Speakers, 100 Watts Freq Res: 50Hz - 20KHz, one woofer & 1/2" tweeter, 89dB, Dimintions: (HxWxD) 9" x 6-1/16" x 5-7/16" Colour, part code options: One (Black) / OneSI (Silver)	JB-CtrlOne	
JBL	<b>Northridge E10 - Pair</b> Pair of 2-way 4" Bookshelf/Wallmount Satellite Speakers 100 Watts, Freq Res: 75Hz - 20KHz, 2kHx crossover, 4" woofer & 3/4" tweeter, 86dB, Dimintions: (HxWxD) 10" x 10-1/8" x 5-1/4", Weight: 3.6kg Colour part code options: <b>E10</b> (Black Ash) / <b>E10BE</b> (Beech) / <b>E10CH</b> (Cherrv)	JB-E10	
JBL	<b>Northridge E30 - Pair</b> Pair of 2-way 6" Bookshelf Speakers 125 Watts, Freq Res: 50Hz - 20KHz, 4kHx crossover, 6" woofer & 3/4" tweeter, 88dB, Dimintions: (HxWxD) 15" x 8-7/8" x 12-1/2", Weight: 7.5kg Colour part code options: <b>E30</b> (Black Ash) / <b>E30BE</b> (Beech) / <b>E30CH</b> (Cherrv)	JB-E30	
<b>Floor Standing Speakers</b>			
JBL	<b>Northridge E80</b> 1x 3-way Dual 6" Floorstanding Speaker 200 Watts, Freq Res: 38Hz - 20KHz, 300Hz & 4kHx crossover, Dual 6" woofer & 3/4" tweeter, 91dB, Dimintions: (HxWxD) 36-1/2" x 8-3/4" x 13-3/4", Weight: 19.1kg Colour part code options: <b>E80</b> (Black Ash) / <b>E80BE</b> (Beech) / <b>E80CH</b> (Cherrv) / <b>E80SI</b> (Silver)	JB-E80	
<b>Indoor / Outdoor Speakers</b>			
<b>4" &amp; 4.25" Indoor / Outdoor Speakers</b>			
Phoenix Gold	<b>LS 100 4.25" In/Outdoor Speaker - Black Pair</b> 3 way with 2" polycarbonate midrange, 1in dome tweeter 50W, Dimensions: 4.75in D x 5.25in W x 8in H Includes wall mounting brackets	PH-LS-100	
Phoenix Gold	<b>LS 200 4.25" In/Outdoor Speakers - White Pair</b> 3 way with 2" polycarbonate midrange, 1in dome tweeter 50W, Dimensions: 4.75in D x 5.25in W x 8in H Includes wall mounting brackets	PH-LS-200	
Phoenix Gold	<b>LS 300 4.25" In/Outdoor Speaker - Black Pair</b> with 3/4" polycarbonate tweeter, 100W, Frequency Response: 70Hz - 20kHz, Sensitivity: 89dB Dimensions: 5.5" D x 5.875" W x 8.25" H Includes wall mounting brackets	PH-LS-300	

Version x.x Month 200X



ADI is a tradename of Honeywell XXXXXXXXXXXX.

ADI reserves the right for data changes and/or printing errors.

# Sound & Communications



PLEASE CHECK IF PRODUCTS ARE AVAILABLE IN YOUR COUNTRY BEFORE YOU PLACE YOUR ORDERS

Vendor	Description	ADI Part number	
<i>Phoenix Gold</i>	<b>LS 400 4.25" In/Outdoor Speaker - White Pair</b> with 3/4" polycarbonate tweeter, 100W, Frequency Response: 70Hz - 20kHz, Sensitivity: 89dB Dimensions: 5.5" D x 5.875" W x 8.25" H Includes wall mounting brackets	<b>PH-LS-400</b>	
<i>Proficient</i>	<b>AW400wht 100W 4" Indoor/Outdoor - White Pair</b> with woofer & 3/4" tweeter, includes swivel mounting bracket Freq Res: 55Hz - 20Khz, Sensitivity: 87dB 1W/1m, 8Ω Dimensions: (HxWxD) 7-3/4", 5-1/2", 5-1/2"	<b>C1-AW400wht</b>	
<i>Proficient</i>	<b>AW400blk 100W 4" Indoor/Outdoor - Black pair</b> with woofer & 3/4" tweeter, includes swivel mounting bracket Freq Res: 55Hz - 20Khz, Sensitivity: 87dB 1W/1m, 8Ω Dimensions: (HxWxD) 7-3/4" x 5-1/2" x 5-1/2"	<b>C1-AW400blk</b>	
<b>5.25" Indoor / Outdoor Speakers</b>			
<i>Phoenix Gold</i>	<b>ATO5 5.25" In/Outdoor Speaker - White Pair</b> with 3/4" polycarbonate tweeter, 125W Frequency Response: 60Hz - 20kHz, Sensitivity: 89dB, Dimensions: 6.675in D x 7.0in W x 9.5in H Includes wall mounting brackets	<b>PH-AT-O5</b>	
<i>Phoenix Gold</i>	<b>LS 525 5.25" In/Outdoor Speaker - Black Pair</b> with 3/4" polycarbonate tweeter, 125W, Frequency Response: 60Hz - 20kHz, Sensitivity: 89dB Dimensions: 6.675" D x 7.0" W x 9.5" H Includes wall mounting brackets	<b>PH-LS-525</b>	
<i>Phoenix Gold</i>	<b>LS 545 5.25" In/Outdoor Speaker - White Pair</b> with 3/4" polycarbonate tweeter, 125W, Frequency Response: 60Hz - 20kHz, Sensitivity: 89dB Dimensions: 6.675" D x 7.0" W x 9.5" H Includes wall mounting brackets	<b>PH-LS-545</b>	
<i>Proficient</i>	<b>AW500TTwht 100W 5-1/4" Stereo In/Outdoor (White x1),</b> with one woofer and two 1" pivoting tweeters, includes swivel mounting bracket, Freq Res: 38Hz - 20Khz, Sensitivity: 89dB 1W/1m, 4Ω Dimensions: (HxWxD) 11" x 7" x 6-1/4"	<b>C1-AW500TTwht</b>	
<i>Proficient</i>	<b>AW500TTblk 100W 5-1/4" Stereo In/Outdoor (Black x1),</b> with one woofer & two 1" pivoting tweeters, includes swivel mounting bracket, Freq Res: 38Hz - 20Khz, Sensitivity: 89dB 1W/1m, 4Ω Dimensions: (HxWxD) 11" x 7" x 6-1/4"	<b>C1-AW500TTblk</b>	
<i>Proficient</i>	<b>AW525blk 125W 5-1/4" Indoor/Outdoor</b> (Black pair), with woofer & 1" pivoting tweeter, includes swivel mounting bracket, Freq Res: 45Hz - 20Khz, Sensitivity: 88dB 1W/1m, 8Ω, Dimensions: (HxWxD) 9-3/16" x 6-1/2" x 6-3/8"	<b>C1-AW525blk</b>	
<b>6.5" Indoor / Outdoor Speakers</b>			
<i>Proficient</i>	<b>AW600TTblk 150W 6-1/2" Stereo In/Outdoor(Black x1),</b> with one woofer & two 1" pivoting tweeters, includes swivel mounting bracket, Freq Res: 35Hz - 20Khz, Sensitivity: 89dB 1W/1m, 4Ω, Dimensions: (HxWxD) 12" x 7" x 8"	<b>C1-AW600TTblk</b>	
<b>Subwoofers</b>			
<i>Proficient</i>	<b>S8 80W 8" Active Subwoofer</b> with twin front-firing ports, 110 / 220Vac voltage with accessible fuse, Freq Res: 45Hz - 200Hz, Dimensions: (HxWxD) 11-3/4" x 9-7/8" x 16-1/2" (add 1-1/4" for feet)	<b>C1-S8</b>	

Version x.x Month 200X

ADI is a tradename of Honeywell XXXXXXXXXXXX.

ADI reserves the right for data changes and/or printing errors.

# Sound & Communications



PLEASE CHECK IF PRODUCTS ARE AVAILABLE IN YOUR COUNTRY BEFORE YOU PLACE YOUR ORDERS

Vendor	Description	ADI Part number	
<i>Proficient</i>	<b>S10 120W 10" Active Subwoofer</b> with twin front-firing ports, 110 / 220Vac voltage with accessible fuse, Freq Res: 32Hz - 200Hz, Dimensions: (HxWxD) 14-1/2" x 11-1/2" x 16-1/8" (add 1-1/4" for feet)	<b>C1-S10</b>	
<i>Phoenix Gold</i>	<b>ASTSUB10 150 Watt 10" Powered Subwoofer</b> Down Firing Low Boy with Side Port, Volume Control and Phase Shift, Crossover By-Pass Switch, Auto On Sensing Unique Gloss Lacquer Finish	<b>PH-AST-SUB10</b>	
<i>JBL</i>	<b>Northridge E150P/230</b> 1x 10" 150Watt Powered Subwoofer (230V) 150 Watts, Freq Res: 50Hz - 20KHz, 4kHz cross over Dual 6" woofer, 5" Midrange & 3/4" tweeter, 90dB, Dimensions: (HxWxD) 10" x 18" x 10", Weight: 7.1kg Colour part code options: <b>E150P</b> (Black Ash) / <b>E150PBE</b> (Beech) / <b>E150PCH</b> (Cherry) / <b>E150PSI</b> (Silver)	<b>JB-E150P/230</b>	
<b>Cinema / Home Theatre Systems</b>			
<i>Phoenix Gold</i>	<b>AST-220S Center Channel Speaker Pair</b> with Dual 4.2" mid, 1" soft dome tweeter, 8 ohm, Sensitivity: 89dB / @ 2.83V / 1m, 15-200 Watts, Freq Res: ±2.5dB from 90-20 kHz (-6dB @72Hz) Dimensions: 3.5"D x 5.25"W x 20.25"H, Includes wall mounting brackets and hardware	<b>PH-AST-220S</b>	
<i>Phoenix Gold</i>	<b>AST BASE</b> Base for AST220S Satellite Speakers Pair Heavy duty metal base for table top application	<b>PH-AST-BASE</b>	
<i>Phoenix Gold</i>	<b>AST STAND</b> Stands for AST220S Satellite Speakers Pair Height with out speaker: 27" Base Dimensions: 9" Diameter x 1.25" H	<b>PH-AST-STAND</b>	
<i>JBL</i>	<b>SCS 200.5 5.1 Simply Cinema Speaker System - SCS™ Series</b> 8" 100 Watt Powered Subwoofer, 3" Satellites, Dual 3" Center JBL EOS™ Waveguide, PolyPlas™ Drivers. Shelf Stands and LFE Cable inc. Colour: Silver Grey & Dark Silver Grey	<b>JB-SCS-200.5</b>	
<i>JBL</i>	<b>FS1000 Pair of Floor stands for SCS 200.5 Satellites</b> Colour part code option: <b>FS1000</b> (Silver Grey & Dark Silver Grey) <b>FS1000BK</b> / <b>FS1000WH</b>	<b>JB-FS1000</b>	
<b>Centre Speakers</b>			
<i>JBL</i>	<b>Northridge EC25</b> 1x 2-way Dual 5" Center Channel Speaker Colour part code options: <b>EC25</b> (Black Ash) / <b>EC25BE</b> (Beech) / <b>EC25CH</b> (Cherry) / <b>EC25SI</b> (Silver)	<b>JB-EC25</b>	
<i>Phoenix Gold</i>	<b>AST220C Home Theater Satellite Speaker</b> with Dual 4.25" mid, 1" soft dome tweeter, 8 ohm, Sensitivity: 89dB / @ 2.83V / 1m, 15 - 200Watts Freq Res: ±2.5dB from 90-20 kHz (-6dB @72Hz) Dimensions: 3.5"D x 5.25"W x 20.25"H Includes wall mounting brackets and hardware	<b>PH-AST-220C</b>	

Version x.x Month 200X

ADI is a tradename of Honeywell XXXXXXXXXXXX.

ADI reserves the right for data changes and/or printing errors.