

## PASSIVE INFRARED DETECTORS

Vendor	Description
<b>CLASSIC</b>	
<b>B0790</b>	<b>Ademco Vision AD</b> Range 15m x 15m with tamper and temperature compensation, 2 year warranty
<b>B0809</b>	<b>Vi Motion</b> True Digital FM processing for superior performance, TMR processing with event selection for superior false alarm protection, no "dead spot", 222 detection patterns range 12m x 12m, 1 year warranty
<b>B0800</b>	<b>Rayo-SA</b> Range 15m x 15m, with cylindrical lens, temperature compensation and tamper switch, selection of 4 interchangeable lenses available, 1 year warranty
<b>B0708</b>	<b>IS 215TCE</b> Intellisense PIR, range 12m x 12m with look-down zone, bug guard and white light immunity, 5 year warranty
<b>B0970</b>	<b>KX15ED</b> Range 15m x 15m, Dual sensor, Automatic Temperature Compensation (ATC), Ceiling /Wall mount bracket included, selectable EOL resistor
<b>B0723</b>	<b>Next</b> True Motion Recognition (TMR) processor based PIR using digital technology, Range 12m x 12m, 3 dimensional lens for reliable catch performance, Creep zone
<b>B0726</b>	<b>Discovery</b> Range 15m x 15m, With cylindrical lens, stylish PIR with integral swivel bracket. Adjustable 1, 2 and 3 pulse counter. Temp Comp.
<b>B1153</b>	<b>IS2560TC</b> Range 26m x 18m, with look down zone, stylish PIR compatible with SMB brackets, 5 year warranty
<b>B0750</b>	<b>Miniature CLIP 1</b> Selectable APPC. 100° 9m x 13,5m. Switchable walk-test LED. Tamper Switch
<b>B0724</b>	<b>SRN-2000</b> Range 18m x 18m Wide Angle. Selectable pulse count and range control. 45 Interchangeable lenses.
<b>QUAD</b>	
<b>B0727</b>	<b>Q-logic</b> Range 15m x 15m, Wide angle, true Quad PIR with true motion recognition (TMR) signal processing
<b>PET IMMUNE</b>	
<b>B0725</b>	<b>K9-40</b> Visonic's patented "Target Specific Imaging™" optical system (TSI) and unique pet identification lenses, the K-940 has an unprecedented capability to distinguish between humans and animals weighing up to 18 kg.
<b>B0661</b>	<b>MX-300</b> Range 10.6m x 13.7 pet immunity up to 18kg.
<b>B0969</b>	<b>KX10DP</b> 15Kg Pet immunity, 10m x 10m, Dual sensor, Automatic Temperature Compensation (ATC), Digital processing, Selectable EOL resistor
<b>B0728</b>	<b>K9-80</b> Pet immune up to 36 kg, 12m x 12 m, Wall and ceiling mount bracket included.

## Vendor

## Description

**PET IMMUNE** (continued)

**B0860** **Next K9-85**  
Pet immunity up to 38 kg, range 12m x 12m, for residential and light commercial applications, Creep zone

**B0779** **DT-7435**  
DUALTECH, Infrared & Microwave Motion Sensor, Pet Immunity up to 45 kg, 10,6m x 12,1m.



NEXT K9-85

**VERTICAL CURTAIN**

**B0971** **KX18EC**  
18 meter Vertical Curtain PIR, selectable EOL resistor, Ceiling/Wall mount bracket included , optional 30 Meter long range lens included

**B1152** **IS25100TC**  
Vertical infrared detector range 30m x 6m, compatible with SMB brackets, 5 year warranty

**B0752** **Clip 4 CH**  
Is the world's smallest, most inconspicuous digital curtain detector, packing into its small elegant housing all the performance of a full-size curtain 2,4,6m curtain coverage.

**B0751** **CH-1000**  
Is a multi-purpose curtain PIR designed for a wide variety of residential, commercial and light industrial applications. CH-1000 is ideal for protection of display windows, walls, skylights, wide entrances, corridors 13,5 x 6m Solid curtain coverage.

**REQUEST TO EXIT**

**B0798** **IS-310**  
For every access control application, Adjustable relay time, Micro-based signal processing, Adjustable shutters, Advanced features include, Piezo sounder, Door contact input Reader/ keypad/key switch input, Remote arming and sounder inputs, Monitor Door and Fail Safe/ Secure modes



IS25100TC



DT-7435

Vendor	Description
--------	-------------

**REQUEST TO EXIT** *(continued)*

<b>B0799</b>	<b>IS-320</b> For every access control application, Adjustable relay time, Micro-based signal processing, Adjustable shutters, Advanced features include, Piezo sounder, Door contact input Reader/ keypad/key switch input, Remote arming and sounder inputs, Monitor Door and Fail Safe/ Secure modes
--------------	--

## DUAL TECHNOLOGY

**CLASSIC**

<b>B0779</b>	<b>DT-7435</b> DUALTECH, Infrared & Microwave Motion Sensor, Pet Immunity up to 45 kg, 10,6m x 12,1m.
<b>B0780</b>	<b>DT-7450</b> Designed for tough, commercial environments, the DT-7450 Motion Sensor achieves reliable protection with improved false alarm immunity through DualCore™ signal processing. Optimum performance is achieved using K-Band microwave technology, 15,2m x 18,2m.
<b>B0730</b>	<b>DUO 200</b> Dual technology PIR and microwave combination detector, true motion recognition (TMR), 12m x 12m
<b>B0729</b>	<b>DUET</b> Dual technology PIR and microwave combination detector, signal processing, 18m x 18m coverage.

**ANTI-MASKING**

<b>B0781</b>	<b>DT-7550</b> DUALTECH, Anti-Masking, Mask Alert anti-mask processing, 15,2m x 18,2m.	
<b>B0732</b>	<b>DUO 220 AM</b> Dual Technology Pir & Microwave combination with TMR, 12m x 12m with dual creep zone and anti-masking.	
<b>B0766</b>	<b>DT 900</b> DUALTECH, range 27m x 21m, for Commercial and Industrial applications, Anti-Masking and Zero Clearance bug guard	
<b>B0767</b>	<b>DT 906</b> DUALTECH, long range 61m x 3m, for Commercial and Industrial corridor applications, Anti-Masking and Zero Clearance bug guard	