

It's tough at the top

Pan & Tilts, Telemetry

For orders Call: 0860 22 55 23

ADI Part number	Vendor	Description
TELEMETRY CONTROL		
TELEMETRY RECEIVERS		
C0742	MICROCO-DEC485	Videotec Telemetry Receiver Fixed Speed, RS485, Mini Telemetry Receiver/Driver, 8 Functions, 24Vac (Can be mounted in camera housing)
C0741	DTRXDC	Videotec Telemetry Receiver Variable Speed, RS485, Telemetry Receiver/Driver, Multi Function, Pre-Sets, IP56, 24Vdc.(Use with PTH355 Pan Tilt Head)
C0740	DTRX324	Videotec Telemetry Receiver Variable Speed, RS485 Telemetry Receiver/Driver, Multi Function, Pre-Sets, IP56, Alarm I/O, 24Vac or 220Vac, (Use with PTH24 Pan Tilt Head)
C0745	VST-400	VST Universal Telemetry Receiver for 24VDC and 24VAC Pan/Tilt Head. Supports VST, Maxpro/Ultrak, Pelco, AFSK, Videor Technicale, Diamond and Panasonic Communication Protocols.128 Preset Positions, Auto Home, 2 Alarm I/P, 6 Relay O/P. Serial data channel for camera control. Dynamic and Thermal overload protection. Unique Soft Start for fine positioning and minimum stress on Pan/Tilt mechanical drive train. Requires 24VAC supply at 2.5 Amps. PCB ONLY. Requires VST-401 to support AFSK.
C0746	VST-403	VST Dynamic Privacy Zone Module for the VST-400 Universal Telemetry Receiver. Dynamic privacy zones are areas within a camera view that are private or restricted. These areas are masked with either Black or Opaque video. This ensures that the CCTV operator is not able to view or record images within the privacy zones. In the Opaque mode the operator will see movement within the privacy zone, with this movement being low resolution such that no detail is available but only the outline of the object passing through the zone. Features include: 40 individual dynamic privacy zones per VST-403 Module, Suitable for zoom ratios from 8 to 16, Dynamic resizing of the privacy zone based on zoom position, Dynamic positioning of the privacy zone based on pan and tilt position, Ease of setup (same as setting a preset view). Plugs into and is powered from the VST-400.



Mitre housing with integral wiper and infra red lamps, mounted on Topper pan & tilt. Razor wire optional.

On a prison wall looking in, or a power station looking out, in fact on any installation that calls for outstanding quality and uncompromising reliability, chances are you'll catch the profile of a MAD pan & tilt. Available in three sizes, from the mighty Homburg, capable of supporting 45kg over the top and a staggering 50kg side-mounted, to the Topper and miniature Bowler, each has a continuous rotation option with housings and accessories to match.

Unique in the industry, we design, manufacture and assemble under one roof, so can provide unrivalled flexibility and support, whilst keeping costs down.

As if this were not enough, we now offer two ranges of specialist equipment.

The all stainless steel NX series for highly corrosive environments, and the ATEX certified, explosion proof EX series. If you're making tough decisions, there's never been a better time to go MAD...



Don't get even. Get MAD

www.madcctv.com



ADI Part number	Vendor	Description
PAN TILT HEADS		
EXTERNAL AC PAN TILT HEADS		
VIDEOTEC RANGE		
C0702	PTH355	Videotec Indoor/Outdoor Pan Tilt Head Light Duty Variable Speed Pan Tilt Head, 12Kg Load, IP66, 30Deg/Sec, Side Mount, Pre-Sets, 24Vdc
C0703	PTH911P	Videotec Indoor/Outdoor Pan Tilt Head Medium Duty Fixed Speed Pan Tilt Head, 30Kg Load, IP66, 6Deg/Sec, Side Mount, Pre-Sets, 24Vac



DM/2000-233

DENNARD RANGE		
DM/2000-233	Dennard Indoor/Outdoor Pan Tilt Head	Medium Duty Fixed Speed Pan Tilt Head, 12Deg/Sec Pan, 3Deg/Sec Tilt, Over the Top Mount, 24Vac with Presets and Long Life Potentiometers

EXTERNAL DC VARIABLE SPEED PAN TILT HEADS		
The Dennard 2000 range is Innovative in design combined with advanced production techniques and modern styling make this unit the benchmark for the next generation of pan & tilt heads.		
Offered with externally adjustable limit switches and Pre-set positions. Ease of maintenance and servicing has been significantly improved over conventional pan & tilt designs. All external fixings are the same size. Options and accessories can be retro-fitted with plug-in wiring.		
Type 2000 pan & tilt heads can be operated upright or inverted and are available in the following range of voltages: 230Va.c, 24Va.c and 24Vd.c.		

DENNARD RANGE		
	DM/2000-309	Dennard Outdoor Pan Tilt Head Medium Duty Variable Speed Pan Tilt Head, 48Deg/Sec Pan, 16Deg/Sec Tilt, Over the Top Mount, 24Vdc with Presets and Long Life Potentiometers



	DM/2000-310	Dennard Outdoor Pan Tilt Head Medium Duty Variable Speed Pan Tilt Head, 48Deg/Sec Pan, 16Deg/Sec Tilt, Continuous Rotation , Over the Top Mount, 24Vdc with Presets and Long Life Potentiometers
--	--------------------	---

MAD RANGE		
C0707	615P/32/12/OTT	MAD Topper Pan Tilt Head 24VDC Variable Speed 32 Deg/Sec Pan, 12 Deg/Sec Tilt, Over the Top Housing Mount, Medium Duty
C0708	615PCR/32/12/OTT	MAD Topper Pan Tilt Head 24VDC Variable Speed 32 Deg/Sec Pan, 12Deg/Sec Tilt, Continuous Rotation , Over the Top Housing Mount, Medium Duty



Videotec Ulisse UPT2SV

CCTV UNIVERSAL LANGUAGE



ULISSE NEW POSITIONING UNIT

ULISSE, the new positioning unit integrates a high performance P&T head with a camera housing and a telemetry receiver. Ideal for outdoor applications like city centre schemes, traffic monitoring and perimeter surveillance.

- > Continuous horizontal rotation, max 100°/s speed
- > Vertical rotation, from -90° to +40°, max 40°/s speed
- > Multi-protocol communications
- > Variable speed autopan, preset and patrol
- > Alarm inputs
- > Available model for IR illuminators fitting
- > 0,02° tracking accuracy on preset positions recalling
- > Optional integrated day/night 36x camera
- > Dynamic video masking of different areas (with integrated camera)
- > Optional wiper and washer
- > Weatherproof standard IP66



www.videotec.com



For further information contact us:

HEADQUARTERS ITALY
VIDEOTEC S.p.A.
Tel. +39 0445.697411
info@videotec.com

UK / IRELAND
VIDEOTEC UK SALES
Tel. +44 02392.477621
uksales@videotec.com

FRANCE
VIDEOTEC FRANCE S.A.R.L.
Tel. +33 2 32094990
videotec.yr@wanadoo.fr

U.S.A. / CANADA
VIDEOTEC SECURITY, Inc.
Tel. +1 973 5950788
usasales@videotec.com

ASIA PACIFIC
VIDEOTEC (HK) LTD
Tel. +852 2330.3601
info@videotec.com.hk



ADI Part number	Vendor	Description
VIDEOTEC RANGE		
C0705	UPT2SGRA000	Videotec ULISSE Indoor/Outdoor Integrated PT Head High Spec, Variable Speed Pan Tilt Unit, IP66, 20Kg Load, 100deg/sec, Continuous Rotation, Internal Telemetry Receiver, Tours, Patterns, Pre-Sets, Masking, RS232 Programming, RS422/485 Control, Large Housing , Sun Shield, Heater.
C0706	UPT2SVSA000	Videotec ULISSE Indoor/Outdoor Integrated PT Head High Spec, Variable Speed Pan Tilt Unit, IP66, 20Kg Load, 100deg/sec, Continuous Rotation, Internal Telemetry Receiver, Tours, Patterns, Pre-Sets, Masking, RS232 Programming, RS422/485 Control, Side Opening Housing, Sun Shield, Heater
C0704	UPT2PVSA000	Videotec ULISSE Indoor/Outdoor Integrated PT Head As Above with Integrated Sony Day/Night Ex View 26X zoom Camera Module
EXTERNAL PAN TILT HEAD BRACKETS		
DENNARD RANGE		
	DM/436	Dennard Wall Mount Bracket for Pan tilt Heads, 20kg Load
	DM/436/CB	Dennard Corner Mount Adaptor for 436 Wall Mount Bracket
	DM/426-250mm	Dennard Ceiling/Column Bracket Medium duty spacer for Pan and Tilts
	DM/160	Dennard Pole Mount Adaptor for 60mm - 90mm diameter poles (Use with 436 Wall Mount Bracket)
	DM/165	Dennard Pole Mount Adaptor for 90mm - 130mm diameter poles (Use with 436 Wall Mount Bracket)
MAD RANGE		
	704	MAD Pan Tilt Wall Mount Bracket Stetson Medium Duty (Two Part Bracket for Topper PT Head)
VIDEOTEC RANGE		
C0709	PTAC	Videotec Pan Tilt Wall Mount Bracket Medium Duty, 100mm 4" PCD fixing, 35kg max load, 400mm long (Use with PTH355)
C0710	PTBC	Videotec Pan Tilt Wall Mount Bracket Heavy Duty, 100mm 4" PCD fixing, 50kg max load, 458mm long (Use with PTH900)
C0712	UPTWBA	Videotec Wall Mount Bracket for ULISSE PTZ
C0713	UPTWBTA	Videotec Parapet Mount Bracket for ULISSE PTZ
C0711	PTCC	Videotec Pole Mount Adaptor (80 -150mm) bracket for external pan & tilt heads